

ALBA20



HIGH-LIGHTS

- > **OPTIMIZATION AND REDUCTION** of loading angle
- > **EXCELLENT WEIGHT-TO-POWER RATIO**
- > **GRIP BELOW** ground level and unmatched pullout capacity
- > **OPTIMIZED EQUIPMENT HEIGHT**
- > **EXCELLENT VISIBILITY** of grasping hook
- > **END-OF-STROKE DAMPER INTEGRATED** into the arm cylinders

AMPLIROLL® HIGH

ALBA20



OPTIONS




Front hydraulic locks




PANTO rear underrun protection adjustable or fixed




Additional hydraulic lines (for cranes, rear tipper trailer...)



High speed



Hook with mechanical or pneumatic safety latch



Vehicle stability systems



Attachments brackets suited for various truck models

Other options available for custom configuration

FICHEPRODUIT/ALBA20/042021/500EN — oh!studio (fr)

TECHNICAL DATA

For GVW from 26T		A50	A53	A56
	Min. container length (mm)	5 300	5 600	5 900
	Max. container length (mm)	6 200	6 600	6 900
	Container length with fixed RUP (mm)	5 400	5 700	6 000
	Weight (kg)	2 330	2 400	2 500

Subject to technical modification; data not binding.
Chassis recommended. Depending on the market.

+33 (0)4 77 36 28 28
42 avenue de Saint-Étienne – BP70056
42161 Andrézieux-Bouthéon cedex
FRANCE

@marrelsas

MARREL
FASSI GROUP

AMPLIROLL® HIGH

MARREL.COM