

AL8

TELESCOPIC JIB 8T CAPACITY



HIGH-LIGHTS

- > **THE MARREL TILTING FRAME** provides unmatched lifting capacity
- > **OPTIMIZED EQUIPMENT HEIGHT**
- > **OPTIMIZED WEIGHT** for maximum useful load
- > **COMPONENTS SHOT-BLASTED** before assembly
- > **ADAPTABLE TO ALL CHASSIS TYPES**
- > **GREAT DEPTH OF RANGE**

AMPLIROLL® FLEX



OPTIONS



1 Mechanical safety latch



2 Front hydraulic lock



3 PANTO rear underrun protection extendable or fixed



4 Available controls: electrical, radio control



5 Additional hydraulic lines (for cranes, rear tipper trailer...)



6 Vehicle stability systems



7 Attachments brackets suited for various truck models

Other options available for custom configuration

FICHEPRODUIT/AL8/042021/500EN — ohtstudio (fr)

TECHNICAL DATA

For GVW 9 to 15 T		A34	A35	A36	A37	A38	A39	A40	A41
	Min. container length (mm)	3 300	3 300	3 300	3 300	3 300	3 500	3 500	3 500
	Max. container length (mm)	4 400	4 500	4 600	4 800	5 000	5 100	5 200	5 300
	Container length with fixed RUP (mm)	3 900	4 000	4 100	4 200	4 300	4 400	4 500	4 600
	Weight (kg)	1 000	1 000	1 000	1 000	1 030	1 080	1 080	1 080

Subject to technical modification; data not binding.
Depending on the market. Chassis recommended.

+33 (0)4 77 36 28 28

42 avenue de Saint-Étienne – BP70056
42161 Andrézieux-Bouthéon cedex
FRANCE

@marrelsas