FASSI GROUP

AL18PA

TELESCOPIC AND ARTICULATED JIB 18T CAPACITY





- > GREATER RANGE of container lengths
- > WELDED HOOK with pneumatic safety latch
- > THE MARREL TILTING FRAME provides unmatched lifting capacity
- > REDUCTION OF LOADING ANGLE > SHOT BLASTING AND PAINTING before assembly
 - > CUSTOMIZATION: color on demand and wide range of accessories
 - > OPTIMIZED EQUIPMENT HEIGHT
 - > END-OF-STROKE DAMPER **INTEGRATED** into the arm cylinders

AMPLIROLL® HIGH

FICHEPRODUIT/AL18PA/042021/500EN — ohistudio (.fr)

ALTEPA

TELESCOPIC AND ARTICULATED JIB 18T CAPACITY



OPTIONS



Available controls: electrical, radio control



Front hydraulic locks



PANTO rear underrun protection adjustable or fixed



Additional hydraulic lines (for cranes, rear tipper trailer...)



High speed



Vehicle stability systems



Attachments brackets suited for various truck models

Other options available for custom configuration

TECHNICAL DATA

For GVW from 18 T		S44	S45	S46	S47	S48	S49	S50	S51	S52	S53	S54	S55	S56	S57	S58
- LG -	Min. container length (mm)	3 200	3 200	3 200	3 200	3 200	3 500	3 500	3 800	3 800	3 800	3 800	3 800	3 800	3 800	3 900
	Max. container length (mm)	5 500	5 600	5 700	5800	5 900	6 000	6 100	6 200	6 300	6 400	6 500	6 700	6 800	6 900	7 000
	Container length with fixed RUP (mm)	4 900	5 000	5 100	5 200	5 300	5 400	5 500	5 600	5 700	5 800	5 900	6 000	6 100	6 200	6 300
Kg	Weight (kg)	2 100	2 100	2 105	2 105	2 110	2 130	2 135	2 270	2 270	2 275	2 290	2 285	2 285	2 290	2 300

Subject to technical modification; data not binding. Depending on the market. Chassis recommended.

+33 (0)4 77 36 28 28 venue de Saint-Étienne – BP70056 42161 Andrézieux-Bouthéon cedex FRANCE



