

AL28

TELESCOPIC JIB
28T CAPACITY



HIGH-LIGHTS

- > **THE MARRELTILTING FRAME** provides unmatched lifting capacity
- > **SHOT BLASTING AND FINISH** before assembly
- > **ROBUSTNESS** for tough, heavy jobs
- > **PNEUMATIC CONTROLS** in cab
- > **28T CAPACITY** available from the ground

AMPLIROLL® HIGH

AL28

TELESCOPIC JIB
28T CAPACITY




OPTIONS



1 PANTO rear underrun protection adjustable or fixed



2 Additional hydraulic lines (for cranes, rear tipper trailer...)



3 High speed



4 Vehicle stability systems

Other options available for custom configuration

FICHEPRODUIT/AL28/042021/500EN — oh!studio (fr)

TECHNICAL DATA

For GVW from 26 T		A56	A58
	Min. container length (mm)	4 700	4 900
	Max. container length (mm)	6 900	7 100
	Container length with fixed RUP (mm)	6 100	6 300
	Weight (kg)	3 130	3 230

Subject to technical modification; data not binding.
Chassis recommended. Depending on the market.

+33 (0)4 77 36 28 28
42 avenue de Saint-Étienne – BP70056
42161 Andrézieux-Bouthéon cedex
FRANCE

@marrelsas

MARREL
FASSI GROUP

AMPLIROLL® HIGH

MARREL.COM