

FASSI GROUP

MB18





- > SEPARATELY AND SIMULTANEOUSLY CONTROLLED telescopic units
- > INTEGRATED STANDS AND UNDERRUN BAR
- > ANTI-CORROSION TREATMENT: shot blasting of fabricated components
- > FRONT PLANKING WITH ADAPTABLE TRAYS
- > SIDE AND FRONT CONTAINER CHOCKING
- > APPROVED LIFTING CHAINS and swivels with safety latch

FICHEPRODUIT/MB18/042021/500EN — ohistudio (.fr)



OPTIONS



Available controls: radio control



Skiploader on cradle




Roller stands or pivoting runners



High speed



Rear spreader with 1 or 2 hooks



Rear chains for better tilting



Attachments brackets suited for various truck models

Other options available for custom configuration

TECHNICAL DATA

		FIXED – CROSSBAR	TELESCOPIC
		MB18 XL XLAE	MB18 XLT
Lifting capacity: Container placed on ground			
Depending on loading radius	2 600 mm	18 000 kg	18 000 kg
	3 100 mm	18 000 kg	18 000 kg
	3 200 mm		15 700 kg
	3 825 mm		13 000 kg
Weight		3 100 kg	3 450 kg
Container length (adjustable centering units)		2 030 mm	

Subject to technical modification; data not binding

+33 (0)4 77 36 28 28

42 avenue de Saint-Étienne – BP70056 42161 Andrézieux-Bouthéon cedex FRANCE



