

AL22LP

TELESCOPIC JIB
22T CAPACITY

HEIGHT OF
195 MM
HIGHER <
PRODUCTIVITY

FREE TILTING FRAME
AND BOOSTER
SYSTEM

SMOOTH LIFTING
MANAGEMENT

CAST PARTS
FOR HIGH-STRESS
AREAS



> POWERFUL

Unique tilting frame and boosters system to provide **unmatched lifting capacity**

Higher productivity thanks to the available space

> CONVENIENT

Ease of use thanks to the hydraulics solution with **premium controls** and **sliding pads**

> VERSATILE

Lengths from **49 to 61** available and customization possibilities

> ROBUST

High quality strength steels

AMPLIROLL® HIGH

AL22LP

TELESCOPIC JIB
22T CAPACITY



OPTIONS AND ACCESSORIES



Hooks selection
Heights & types



Rear Hydraulic Locking



Front Hydraulic Boxes & Oiltank



Controls options
• Fast speed
• Sequence control



Free Glide
• Frictionless drive



Crane Base Subframe Prolongation



Rear Underrun Protection
• Fixed • Telescopic
• Panto • Inclined

Additional options & accessories available for customized configuration

TECHNICAL DATA

For GVW from 26 T		S49	S51	S52	S53	S55	S56	S57	S58	S59	S61
	Min. container length (mm)	4 500	4 500	4 600	4 700	4 900	5 000	5 100	5 100	5 200	5 200
	Max. container length (mm)	6 100	6 300	6 400	6 500	6 700	6 800	6 900	7 000	7 100	7 300
	Container length with fixed RUP (mm)	5 100	5 300	5 400	5 500	5 700	5 800	5 900	6 000	6 100	6 300
	Weight (kg)	2 167	2 197	2 244	2 259	2 310	2 358	2 373	2 410	2 430	2 460

Subject to technical modification; data not binding.
Depending on the market. Chassis recommended.

contact@marrel.com
42 avenue de Saint-Étienne – BP70056
42161 Andrézieux-Bouthéon cedex
FRANCE



AMPLIROLL® HIGH

MARREL.COM