




## AMPLIROLL® HIGH

# AL14

TELESCOPIC JIB  
LIFTING CAPACITY **14T**

AMPLI'DRIVE PACKS

-  START
-  OPTI
-  PRO

 **S**  
GENERATION



## KEY POINTS

### POWER

Unmatched lifting capacity thanks to the **Marrel tilting frame**

### ERGONOMICS

**AMPLI'DRIVE control packs** to meet all your needs

### PERFORMANCE

Choose the optional **SOFT POWER** system for proportional movement and optimal comfort


### CUSTOMIZATION

Paint color on request and a wide range of accessories




## OPTIONS


- 1




Ampli'Drive controls: pneumatic, electrical, radio controls
- 2




Front hydraulic locks
- 3




Rear underrun protection (RUP)
- 4




Additional hydraulic lines (for cranes, rear tipper trailer...)
- 5



Hook with mechanical or pneumatic safety latch
- 6



Vehicle stability systems
- 7



Attachments brackets suited for various truck models

Other options available for custom configuration

## TECHNICAL DATA

For GW 15 to 19 T		S40	S41	S42	S43	S44	S45	S46	S47	S48	S49	S50	S51	S52	S53
	Min. container length (mm)	3 700	3 700	3 700	3 700	4 000	3 700	4 000	4 000	4 000	4 000	4 100	4 300	4 300	4 400
	Max. container length (mm)	5 100	5 200	5 300	5 400	5 500	5 600	5 700	5 800	5 900	6 000	6 100	6 200	6 300	6 400
	Container length with fixed RUP (mm)	4 500	4 600	4 700	4 800	4 900	5 000	5 100	5 200	5 300	5 400	5 500	5 600	5 700	5 800
	Weight (kg)	1 650	1 650	1 675	1 675	1 700	1 700	1 725	1 750	1 750	1 750	1 750	1 950	1 950	1 950

For GW 12 to 26 T		S54	S55	S56	S57	S58
	Min. container length (mm)	4 600	4 600	4 600	4 600	4 600
	Max. container length (mm)	6 500	6 700	6 800	6 900	7 000
	Container length with fixed RUP (mm)	5 900	6 000	6 100	6 200	6 300
	Weight (kg)	2 075	2 090	2 095	2 095	2 100

Subject to technical modification; data not binding