MARREL

MARREL.com

AMPLIROLL® HIGH

AL14PA

TELESCOPIC AND ARTICULATED JIB
LIFTING CAPACITY 14T

AMPLI'DRIVE PACKS
START OPTI PRO

S GENERATION

KEY POINTS

POWER

Unmatched lifting capacity thanks to the **Marrel tilting frame**

ERGONOMICS

AMPLI'DRIVE control packs to meet all your needs

PRODUCTIVITY

Reduced loading angle and greater range of container lengths

PERFORMANCE

Choose the optional **SOFT POWER** system for proportional movement and optimal comfort

AMPLIROLL® HIGH
Telescopic and articulated jib

MARREL

OPTIONS

1
Ampli'Drive controls: pneumatic, electrical, radio controls

2
Front hydraulic locks

3
Rear underrun protection (RUP)

4
Additional hydraulic lines (for cranes, rear tipper trailer...)

5 
High-speed

6
Vehicle stability systems

7
Attachments brackets suited for various truck models

Other options available for custom configuration

TECHNICAL DATA

For GVW 15 to 19 T	S44	S45	S46	S47	S48	S49	S50	S51	S52	S53	S54	S55	S56	S57	S58
Min. container length (mm)	3200	3200	3200	3200	3200	3200	3500	3500	3500	3800	3800	3800	3800	3800	3900
Max. container length (mm)	5500	5600	5700	5800	5900	6000	6100	6200	6300	6400	6500	6700	6800	6900	7000
Container length with fixed RUP (mm)	4900	5000	5100	5200	5300	5400	5500	5600	5700	5800	5900	6000	6100	6200	6300
Weight (kg)	1900	1900	1925	1925	1950	1975	1975	1975	2115	2135	2175	2245	2245	2250	2255

Subject to technical modification; data not binding

A FASSI GROUP COMPANY

+33 (0)4 77 36 28 28
42 avenue de Saint-Étienne – BP70056
42161 Andrézieux-Bouthéon cedex - France