

AMPLIROLL® HIGH AL20PA

TELESCOPIC AND ARTICULATED JIB
LIFTING CAPACITY **20T**

AMPLI'DRIVE PACKS

- START
- OPTI
- PRO

S
GENERATION



KEY POINTS

POWER

Unmatched lifting capacity thanks to the **Marrel tilting frame**

PRODUCTIVITY

Reduced loading angle and greater range of container lengths

ERGONOMICS


AMPLI'DRIVE control packs to meet all your needs

PERFORMANCE


Choose the optional **SOFT POWER** system for proportional movement and optimal comfort




OPTIONS

- 


1

Ampli'Drive controls: pneumatic, electrical, radio controls
- 


2

Front hydraulic locks
- 


3

Rear nderrun protection (RUP)
- 


4

Additional hydraulic lines (for cranes, rear tipper trailer...)
- 

5

Hook with mechanical or pneumatic safety latch
- 

6

Vehicle stability systems
- 



7

Attachments brackets suited for various truck models

Other options available for custom configuration

TECHNICAL DATA

For GVW 26 to 32 T		S48	S49	S50	S51	S52	S53	S54	S55	S56	S57	S58	S59	S60
	Min. container length (mm)	3 300	3 300	3 300	3 300	3 600	3 600	3 600	3 900	39 00	3 900	3 900	3 900	4 100
	Max. container length (mm)	5 900	6 000	6 100	6 200	6 300	6 400	6 500	6 600	6 800	6 900	7 000	7 100	7 200
	Container length with fixed RUP (mm)	5 300	5 400	5 500	5 600	5 700	5 800	5 900	6 000	6 100	6 200	6 300	6 400	6 500
	Weight (kg)	2 330	2 335	2 335	2 340	2 460	2 460	2 465	2 485	2 510	2 515	2 515	2 520	2 535

For GVW 26 to 32 T		SL61	SL62	SL63	SL64	SL65	SL66	SL67	SL68
	Min. container length (mm)	4 600	4 600	4 600	5 000	5 000	5 000	5 000	5 000
	Max. container length (mm)	7 300	7 400	7 500	7 600	7 700	7 800	7 900	8 000
	Container length with fixed RUP (mm)	6 600	6 700	6 800	6 900	7 000	7 100	7 200	7 300
	Weight (kg)	2 755	2 785	2 815	2 845	2 875	2 905	2 935	2 965

Subject to technical modification; data not binding