MARREL

MARREL.com

AMPLIROLL® HIGH

AL26PA

TELESCOPIC AND ARTICULATED JIB
LIFTING CAPACITY 26T

AMPLI'DRIVE PACKS
START OPTI PRO

S GENERATION

KEY POINTS

POWER

Unmatched lifting capacity thanks to the **Marrel tilting frame**

ERGONOMICS

AMPLI'DRIVE control packs to meet all your needs

PRODUCTIVITY

Reduced loading angle and greater range of container lengths

PERFORMANCE

Choose the optional **SOFT POWER** system for proportional movement and optimal comfort

AMPLIROLL® HIGH
Telescopic and articulated jib

MARREL

OPTIONS

1
Ampli'Drive controls: pneumatic, electrical, radio controls

2
Front hydraulic locks

3
Rear underrun protection (RUP)

4
Additional hydraulic lines (for cranes, rear tipper trailer...)

5 
High-speed

6 
Vehicle stability systems

7
Attachments brackets suited for various truck models

Other options available for custom configuration

TECHNICAL DATA

For GVW 26 to 32 T	S49	S50	S51	S52	S53	S54	S55	S56	S57	S58	S59	S60
Min. container length (mm)	3 700	3 700	3 700	3 700	4 100	4 100	4 100	4 100	4 100	4 600	4 600	4 600
Max. container length (mm)	6 100	6 200	6 300	6 400	6 500	6 600	6 700	6 800	6 900	7 000	7100	7 200
Container length with fixed RUP (mm)	5 400	5 500	5 600	5 700	5 800	5 900	6 000	6 100	6 200	6 300	6 400	6 500
Weight (kg)	2 740	2 750	2 750	2 750	2 790	2 810	2 810	2 810	2 930	2 940	2 940	2 950

For GVW 26 to 32 T	SL61	SL62	SL63	SL64	SL65	SL66	SL67	SL68
Min. container length (mm)	4 600	4 600	4 600	5 000	5 000	5 000	5 000	5 000
Max. container length (mm)	7 300	7 400	7 500	7 600	7 700	7 800	7 900	8 000
Container length with fixed RUP (mm)	6 600	6 700	6 800	6 900	7 000	7100	7 200	7 300
weight (kg)	2 980	3 010	3 040	3 070	3 100	3 130	3 160	3 190

Subject to technical modification; data not binding

A FASSI GROUP COMPANY

+33 (0)4 77 36 28 28
42 avenue de Saint-Étienne – BP70056
42161 Andrézieux-Bouthéon cedex - France

AMPLIROLL® HIGH
Telescopic and articulated jib