

## AMPLIROLL® HIGH ALBA20PA

TELESCOPIC AND ARTICULATED JIB  
LIFTING CAPACITY **20T**



### KEY POINTS

#### PRODUCTIVITY

Optimization and reduction of the loading angle

#### PERFORMANCE

Below-ground-level picking and **unmatched breakout capacity**

#### SAFETY

Welded hook with **pneumatic safety latch**

#### COMFORT

**End-of-stroke damper** integrated into the arm cylinders



## OPTIONS



High speed




Front hydraulic locks



Rear underrun protection (RUP)



Additional hydraulic lines (for cranes, rear tipper trailer...)



High-speed



Vehicle stability systems



Attachments brackets suited for various truck models



Rear lifter of the loading axis

Other options available for custom configuration

## TECHNICAL DATA

| For GVW from 26 T |                                      | A50  | A53  | A56  |
|-------------------|--------------------------------------|------|------|------|
|                   | Min. container length (mm)           | 4200 | 4500 | 4800 |
|                   | Max. container length (mm)           | 6200 | 6600 | 6900 |
|                   | Container length with fixed RUP (mm) | 5400 | 5700 | 6000 |
|                   | Weight (kg)                          | 2520 | 2570 | 2670 |

Subject to technical modification; data not binding